

2023 MXZ® X-RS®

A non-compromising race-inspired sled capable of taking on the roughest trails with ease.



// WHAT'S NEW

- REV® Gen5 platform (850 E-TEC® only)
- KYB® Pro 40R front shocks

MXZ X-RS
850 E-TEC SHOWN

// PACKAGE HIGHLIGHTS

- Rotax® 850 E-TEC and 600R E-TEC engines
- High-performance KYB® Pro shock package
- RAS™ X front suspension
- rMotion™ X rear suspension
- Electric starter
- RS running boards
- pDrive™ clutch
- Backlit multifunction handlebar controls
- Forward steering post position
- Rack steering system
- Low-profile 90mm riser block
- Transparent handguards
- Open toe-hold
- Pilot X skis

ROTAX ENGINE	850 E-TEC	600R E-TEC
Engine details	Liquid-cooled, two-stroke, eRAVE™	Liquid-cooled, two-stroke, eRAVE
Cylinders - Displacement	2 - 849 cc	2 - 599.4 cc
Bore - Stroke (mm)	82 - 80.4	72.3 - 73
Carburation	E-TEC direct injection with additional booster injectors	E-TEC direct injection
Fuel type - Octane	Unleaded - 95	Unleaded - 95
Fuel tank (L/US gal)	36/9.5	36/9.5
Oil tank capacity (L/qt)	3.4/3.6	3.4/3.6

POWERTRAIN	850 E-TEC	600R E-TEC
Drive clutch	pDrive with clickers	pDrive with clickers
Driven clutch	QRS Vent	QRS
Drive sprocket pitch	73 mm/2.86 in.	73 mm/2.86 in.

DIMENSIONS	850 E-TEC	600R E-TEC
Overall vehicle length	2,925 mm/115.2 in.	
Overall vehicle width	1,209 - 1,232 - 1,255 mm/47.6 - 48.5 - 49.4 in.	
Overall vehicle height	1,267 mm/49.9 in.	
Ski stance	1,090 mm/43 in. adjustable	
Track	Ice Ripper® XT:	
(Length x Width x Profile)	129 x 15 x 1.5 in.	

COLOR	850 E-TEC SHOWN
Platinum Silver / Spartan Red	

SUSPENSION	850 E-TEC SHOWN
Front suspension	RAS X
Front shock	KYB Pro 40 R EA-3
Front suspension travel	265 mm/10.4 in.
Rear suspension	rMotion X
Center shock	KYB Pro 40 R EA-3
Rear shock	KYB Pro 40 R EA-3
Rear suspension travel	292 mm/11.5 in.

FEATURES	850 E-TEC SHOWN
Platform	REV Gen5 (850 E-TEC only) REV Gen4
Skis	Pilot X
Seating	Trail performance
Handlebar	U-shaped aluminum with J-hooks/ Transparent handguards
Riser block height	90 mm/3.5 in.
Starter	Electric
Reverse	RER™
Brake system	Brembo®
Heated throttle lever/grips	Standard
Gauge type	7.2 in. digital display
Windshield	Optional
Runner - Carbide	Round 1/2 - 4 in.
Bumpers (front/rear)	Std/Std

ski-doo

