

# ZR R-XC



## VEHICLE SPECS

### ENGINE

	ZR 858 R-XC EPS	ZR 600 R-XC EPS
Engine Type	858, 2-Stroke	600, 2-Stroke
Displacement <span>?</span>	858cc	599cc
Cooling <span>?</span>	Liquid	Liquid
Cylinders <span>?</span>	2	2
Bore x Stroke <span>?</span>	85 x 75.6 mm	73.8 x 70 mm
Lubrication <span>?</span>	Electronic Injection	Electronic Injection
Ignition	Digitally Controlled CDI	Digitally Controlled CDI
Engine Stator Output <span>?</span>	270W @ 3000 RPM	270W @ 3000 RPM
Fuel Delivery <span>?</span>	Next Gen. C-TEC2	Dual Stage Injection
Exhaust	APV IV w/ Full Stainless Steel Exhaust & EGT Sensors	APV w/ Tuned Pipe, Pipe Sensor, Stainless Steel Manifold & Muffler
Fuel Capacity	10.4 gal	10.4 gal
Oil System Capacity	3 qt	3 qt
Coolant System Capacity	5.4 qt	5.4 qt
Minimum Octane <span>?</span>	91	91

**POWERTRAIN**

	<b>ZR 858 R-XC EPS</b>	<b>ZR 600 R-XC EPS</b>
Drive Clutch <span>?</span>	ADAPT	ADAPT
Driven Clutch <span>?</span>	ADAPT	ADAPT
Drive System	AC Trail Belt Drive	AC Trail Belt Drive
Brakes	Stealth Hydraulic Master Cylinder w/ Race Caliper	Stealth Hydraulic Master Cylinder w/ Race Caliper
Clutch Calibration <span>?</span>	0-5,000 ft	0-5,000 ft
Gearing	30/58	30/58
Chain Pitch	Belt	Belt
Track Drive Sprocket <span>?</span>	9 Tooth, 2.86 Pitch, Exvolute	8 Tooth, 2.86 Pitch, Exvolute
Reverse	Push-Button Engine	Push-Button Engine

**SUSPENSION**


	<b>ZR 858 R-XC EPS</b>	<b>ZR 600 R-XC EPS</b>
Front Suspension	AWS 42	AWS 42
Ski Shocks	Fox QS3R	Fox QS3R
Sway Bar <span>?</span>	Standard	Standard
Front Travel	8.2 in	8.2 in
Rear Suspension	R-XC SLIDE-ACTION w/ 4 Wheel Rear Axle Assembly, Coupling Blocks, Torque-Sensing Link Rear Arm & Adjustable Torsion Springs	R-XC SLIDE-ACTION w/ 4 Wheel Rear Axle Assembly, Coupling Blocks, Torque-Sensing Link Rear Arm & Adjustable Torsion Springs
Front Track Shock	FOX 1.5 QS3	FOX 1.5 QS3
Rear Track Shock	FOX 2.0 ZERO QS3R	FOX 2.0 ZERO QS3R

	ZR 858 R-XC EPS	ZR 600 R-XC EPS
Rear Travel	13.5 in	13.5 in

## DIMENSIONS

	ZR 858 R-XC EPS	ZR 600 R-XC EPS
Overall Chassis Length	126 in	126 in
Overall Chassis Width	48-49 in	48-49 in
Overall Chassis Height	48 in	48 in
Track Type	Cobra	Cobra
Track Width	15 in	15 in
Track Length	137 in	137 in
Lug	1.35 in	1.35 in
Pitch 	2.86 in	2.86 in
Ski Stance	41.5-42.5 in - Adjustable	41.5-42.5 in - Adjustable
Ski Type/Width	C&A Pro XPT	C&A Pro XPT
Runner Type	Woody's Dooly 6 in	Woody's Dooly 6 in

## INSTRUMENTATION

	ZR 858 R-XC EPS	ZR 600 R-XC EPS
Type of Gauge	G8 (CAN w/o Group Ride)	G8 (CAN w/o Group Ride)
Speedometer	Digital	Digital
Tachometer 	Digital	Digital
Odometer	Digital	Digital

	ZR 858 R-XC EPS	ZR 600 R-XC EPS
Fuel	Digital	Digital
Oil	Indicator Light	Indicator Light
Coolant	Digital/Indicator Light	Digital/Indicator Light
Clock	Digital	Digital
Battery Voltage	Digital	Digital
Altimeter	Digital	Digital
Hours	Digital	Digital

## FEATURES

	ZR 858 R-XC EPS	ZR 600 R-XC EPS
Color	Race Green	Race Green
Heat Exchanger <span>?</span>	Front/Long Tunnel	Front/Long Tunnel
Starter	Push-Button Electric Start	Push-Button Electric Start
Handlebars	Hooked	Hooked
Lighting	LED	LED
Seating	Trail	Trail
Standard Accessories	12V Outlet, Sport Front Bumper, Integrated Goggle Holder, ATACH mounting, Handguards, Hand & Thumb Warmers, Race Brake Disc, EPS Steering, Tether Switch, Visor Plug-In	12V Outlet, Sport Front Bumper, Integrated Goggle Holder, ATACH mounting, Handguards, Hand & Thumb Warmers, Race Brake Disc, EPS Steering, Tether Switch, Visor Plug-In
Windshield	5.5 in Low Height	5.5 in Low Height

*Vehicle specifications are subject to change.*