

ZR



VEHICLE SPECS

ENGINE

	ZR 600 SNO PRO EPS SG	ZR 600	ZR 600 SNO PRO	ZR 600 EPS	ZR 600 SNO PRO EPS	ZR 600 SNO PRO EPS SG
Engine Type	600, 2-Stroke	600, 2-Stroke	600, 2-Stroke	600, 2-Stroke	600, 2-Stroke	85
Displacement ?	599cc	599cc	599cc	599cc	599cc	
Cooling ?	Liquid	Liquid	Liquid	Liquid	Liquid	
Cylinders ?	2	2	2	2	2	
Bore x Stroke ?	73.8 x 70 mm	73.8 x 70 mm	73.8 x 70 mm	73.8 x 70 mm	73.8 x 70 mm	85
Lubrication ?	Electronic Injection	Electronic Injection	Electronic Injection	Electronic Injection	Electronic Injection	E
Ignition	Digitally Controlled CDI	Digitally Controlled CDI	Digitally Controlled CDI	Digitally Controlled CDI	Digitally Controlled CDI	Co
Engine Stator Output ?	270W @ 3000 RPM	270W @ 3000 RPM	270W @ 3000 RPM	270W @ 3000 RPM	270W @ 3000 RPM	27
Fuel Delivery ?	Dual Stage Injection	Dual Stage Injection	Dual Stage Injection	Dual Stage Injection	Dual Stage Injection	N
Exhaust	APV w/ Tuned Pipe, Pipe Sensor, Stainless Steel	APV w/ Tuned Pipe, Pipe Sensor, Stainless Steel	APV w/ Tuned Pipe, Pipe Sensor, Stainless Steel	APV w/ Tuned Pipe, Pipe Sensor, Stainless Steel	APV w/ Tuned Pipe, Pipe Sensor, Stainless Steel	AP Sta Ext

	ZR 600 SNO PRO EPS SG	ZR 600	ZR 600 SNO PRO	ZR 600 EPS	ZR 600 SNO PRO EPS	ZR 600 EPS
	Manifold & Muffler	Manifold & Muffler	Manifold & Muffler	Manifold & Muffler	Manifold & Muffler	
Fuel Capacity	10.4 gal	10.4 gal	10.4 gal	10.4 gal	10.4 gal	
Oil System Capacity	3.0 qt	3.0 qt	3.0 qt	3.0 qt	3.0 qt	
Coolant System Capacity	5.4 qt	5.3 or 5.4 qt	5.3 qt or 5.4 qt	5.3 qt or 5.4 qt	5.4 qt	
Minimum Octane ?	91	91	91	91	91	

POWERTRAIN

	ZR 600 SNO PRO EPS SG	ZR 600	ZR 600 SNO PRO	ZR 600 EPS	ZR 600 SNO PRO EPS	ZR 600 EPS
Drive Clutch ?	ADAPT	ADAPT	ADAPT	ADAPT	ADAPT	
Driven Clutch ?	ADAPT	ADAPT	ADAPT	ADAPT	ADAPT	
Drive System	AC Trail Belt Drive	AC Trail Belt Drive	AC Trail Belt Drive	AC Trail Belt Drive	AC Trail Belt Drive	AC Trail Belt Drive
Brakes	Stealth Hydraulic Master Cylinder	Stealth Hydraulic Master Cylinder	Stealth Hydraulic Master Cylinder	Stealth Hydraulic Master Cylinder	Stealth Hydraulic Master Cylinder	Stealth Hydraulic Master Cylinder
Clutch Calibration ?	0-5,000 ft	0-5,000 ft	0-5,000 ft	0-5,000 ft	0-5,000 ft	0-5,000 ft
Gearing	27/60	27/60	27/60	27/60	27/60	27/60
Chain Pitch	Belt	Belt	Belt	Belt	Belt	Belt
Track Drive Sprocket ?	9 Tooth, 2.86 Pitch, Involute	9 Tooth, 2.86 Pitch, Involute	9 Tooth, 2.86 Pitch, Involute	9 Tooth, 2.86 Pitch, Involute	9 Tooth, 2.86 Pitch, Involute	9 Tooth, 2.86 Pitch, Involute

	ZR 600 SNO PRO EPS SG	ZR 600	ZR 600 SNO PRO	ZR 600 EPS	ZR 600 SNO PRO EPS	ZR 600 EPS
Reverse	Push-Button Engine	Push-Button Engine	Push-Button Engine	Push-Button Engine	Push-Button Engine	Push-Button Engine

SUSPENSION

	ZR 600 SNO PRO EPS SG	ZR 600	ZR 600 SNO PRO	ZR 600 EPS	ZR 600 SNO PRO EPS	ZR 600 EPS
Front Suspension	AWS 42	AWS 42	AWS 42	AWS 42	AWS 42	AWS 42
Ski Shocks	AC5S	Fox 1.5 iQS	AC5S	Fox 1.5 iQS	AC5S	Fox 1.5 iQS
Sway Bar ?	Standard	Standard	Standard	Standard	Standard	Standard
Front Travel	8.2 in	8.2 in	8.2 in	8.2 in	8.2 in	8.2 in
Rear Suspension	SLIDE-ACTION with 3 Wheel Rear Axle Assembly, Coupling Blocks, Torque-Sensing Link Rear Arm & Adjustable Torsion Springs	(129)SLIDE-ACTION with 3 Wheel Rear Axle Assembly & Adjustable Torsion Springs (137)SLIDE-ACTION with 3 Wheel Rear Axle Assembly, Coupling Blocks, Torque-Sensing Link Rear Arm & Adjustable Torsion Springs	(129)SLIDE-ACTION with 3 Wheel Rear Axle Assembly & Adjustable Torsion Springs (137)SLIDE-ACTION with 3 Wheel Rear Axle Assembly, Coupling Blocks, Torque-Sensing Link Rear Arm & Adjustable Torsion Springs	(129)SLIDE-ACTION with 3 Wheel Rear Axle Assembly & Adjustable Torsion Springs (137)SLIDE-ACTION with 3 Wheel Rear Axle Assembly, Coupling Blocks, Torque-Sensing Link Rear Arm & Adjustable Torsion Springs	SLIDE-ACTION with 3 Wheel Rear Axle Assembly, Coupling Blocks, Torque-Sensing Link Rear Arm & Adjustable Torsion Springs	SLIDE-ACTION with 3 Wheel Rear Axle Assembly, Coupling Blocks, Torque-Sensing Link Rear Arm & Adjustable Torsion Springs
Front Track Shock	AC5S	Arctic Cat IFP 1.5	AC5S	Arctic Cat IFP 1.5	AC5S	Arctic Cat IFP 1.5
Rear Track Shock	AC5S	Fox 2.0 iQS	AC5S	Fox 2.0 iQS	AC5S	Fox 2.0 iQS

	ZR 600 SNO PRO EPS SG	ZR 600	ZR 600 SNO PRO	ZR 600 EPS	ZR 600 SNO PRO EPS	ZR 600 EPS
Rear Travel	13.5 in	13.5 in	13.5 in	13.5 in	13.5 in	13.5 in

DIMENSIONS

	ZR 600 SNO PRO EPS SG	ZR 600	ZR 600 SNO PRO	ZR 600 EPS	ZR 600 SNO PRO EPS	ZR 600 EPS
Overall Chassis Length	126 in	118 in or 126 in	118 in or 126 in	118 in or 126 in	126 in	126 in
Overall Chassis Width	48-49 in	48-49 in	48-49 in	48-49 in	48-49 in	48-49 in
Overall Chassis Height	47 in	47 in	47 in	47 in	47 in	47 in
Track Type	Ripsaw II	Ripsaw or Ripsaw II	Ripsaw or Ripsaw II	Ripsaw or Ripsaw II	Ripsaw II	Ripsaw II
Track Width	15 in	15 in	15 in	15 in	15 in	15 in
Track Length	137 in	129 in or 137 in	129 in or 137 in	129 in or 137 in	137 in	137 in
Lug	1.25 in	1.25 in	1.25 in	1.25 in	1.25 in	1.25 in
Pitch ?	2.86 in	2.86 in	2.86 in	2.86 in	2.86 in	2.86 in
Ski Stance	41.5-42.5 in - Adjustable	41.5-42.5 in - Adjustable	41.5-42.5 in - Adjustable	41.5-42.5 in - Adjustable	41.5-42.5 in - Adjustable	41.5-42.5 in - Adjustable
Ski Type/Width	Trail - 6 in	Trail - 6 in	Trail - 6 in	Trail - 6 in	Trail - 6 in	Trail - 6 in
Runner Type	Long Dual Runner 4-Bolt w/ Carbide	Long Dual Runner 4-Bolt w/ Carbide	Long Dual Runner 4-Bolt w/ Carbide	Long Dual Runner 4-Bolt w/ Carbide	Long Dual Runner 4-Bolt w/ Carbide	Long Dual Runner 4-Bolt w/ Carbide

INSTRUMENTATION

	ZR 600 SNO PRO EPS SG	ZR 600	ZR 600 SNO PRO	ZR 600 EPS	ZR 600 SNO PRO EPS	Z
Type of Gauge	G8 (CAN w/o Group Ride)	Deluxe	Sport	G8 (CAN w/o Group Ride)	G8 (CAN w/o Group Ride)	
Speedometer	Digital	Digital	Digital	Digital	Digital	
Tachometer ?	Digital	Digital	Digital	Digital	Digital	
Odometer	Digital	Digital	Digital	Digital	Digital	
Fuel	Digital	Digital	Digital	Digital	Digital	
Oil	Digital	Digital	LCD Icon	Digital	Digital	
Coolant	LCD Icon	LCD Icon	Digital bar graph	LCD Icon	LCD Icon	
Clock	Digital	Digital	N/A	Digital	Digital	
Battery Voltage	Digital	Digital	N/A	Digital	Digital	
Altimeter	Digital	Digital	N/A	Digital	Digital	
Hours	Digital	Digital	Digital	Digital	Digital	

FEATURES

	ZR 600 SNO PRO EPS SG	ZR 600	ZR 600 SNO PRO	ZR 600 EPS	ZR 600 SNO PRO EPS	Z
Color	White	Black/Green	Black/Green	Black/Green	Black/Green	Bl
Heat Exchanger ?	Front Long Tunnel	Front Long Tunnel	Front Long Tunnel	Front Long Tunnel	Front Long Tunnel	F
Starter	Push-Button Electric Start	Push-Button Electric Start	Push-Button Electric Start	Push-Button Electric Start	Push-Button Electric Start	Pe El
Handlebars	Hooked	Hooked	Hooked	Hooked	Hooked	

	ZR 600 SNO PRO EPS SG	ZR 600	ZR 600 SNO PRO	ZR 600 EPS	ZR 600 SNO PRO EPS	ZR 600 EPS
Lighting	LED	LED	LED	LED	LED	
Seating	Trail	Trail	Trail	Trail	Trail	
Standard Accessories	12V Outlet, Sport Front Bumper, Integrated Goggle Holder, ATACH mounting, Hand & Thumb Warmers, Standard Brake Disc, EPS Steering, Tether Switch, Visor Plug-In	12V Outlet, Sport Front Bumper, Integrated Goggle Holder, ATACH mounting, Hand & Thumb Warmers, Standard Brake Disc, Ratio Steering, Tether Switch, Visor Plug-In	12V Outlet, Sport Front Bumper, Integrated Goggle Holder, ATACH mounting, Hand & Thumb Warmers, Standard Brake Disc, Ratio Steering, Tether Switch, Visor Plug-In	12V Outlet, Sport Front Bumper, Integrated Goggle Holder, ATACH mounting, Hand & Thumb Warmers, Standard Brake Disc, EPS Steering, Tether Switch, Visor Plug-In	12V Outlet, Sport Front Bumper, Integrated Goggle Holder, ATACH mounting, Hand & Thumb Warmers, Standard Brake Disc, EPS Steering, Tether Switch, Visor Plug-In	12V Outlet, Sport Front Bumper, Integrated Goggle Holder, ATACH mounting, Hand & Thumb Warmers, Standard Brake Disc, EPS Steering, Tether Switch, Visor Plug-In
Windshield	Mid Height	Mid Height	Mid Height	Mid Height	Mid Height	Mid Height

Vehicle specifications are subject to change.